

# Black Neoprene Rubber



## DRC-20 DATA SHEET

**DELTA RUBBER LIMITED**

Unit 21 Priory Industrial Park, Airspeed Road  
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

### Description

DRC-20 Black commercial quality Neoprene 65° sh A material.

### Technical Information

Material:	Chloroprene/SBR CQ Grade
Application:	General Purpose, Water/UV/Oil/Fuel Resistant
Thickness:	1.0,1.5,2,3,4,5,6,8,10,12,15,20,25mm
Colour:	Black
Cloth/Plate Finish:	Plate
Density [specific gravity]:	1.4g/cm <sup>3</sup>
Hardness [Degrees Shore A]:	60° ± 5°
Tensile Strength [MPA]:	5.0 min
Elongation at Break:	300%
Minimum Temperature:	-20°C
Maximum Temperature:	+110°C
Compression Set:	35%
Tear Resistance (kg/cm):	20

#### Thickness

1.0mm – 25mm

(other thicknesses on request)

#### Sheet Size

1.4m wide x 5, 10 or 20m rolls

#### Finish

Plate Finish

#### Cutting

Standard Press Tools

