

DATA SHEET



Black Polyurethane Rubber 60°sh A

**Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD**

Tel: 01425 278011

Fax: 01425 278012

www.deltarubber.co.uk

deltasales@deltarubber.co.uk

Description

Polyurethane is a high performance synthetic rubber, with excellent abrasion resistance, tear strength, toughness and durability. Our Black Polyurethane is a 60° shore A material, suitable for a wide range of applications with good aging, chemical, oil & solvent resistance. Thickness: 1.5mm to 10mm (other thickness on request)

- **Sheet size: 500m wide x 2400m rolls**
- **Finish: Plate Finish**
- **Cutting: Standard Press- Tools**

Technical Information

Material:	Polyurethane
Application:	General Purpose, mechanical, shock & pressure pads.
Thickness:	1.5, 2, 3, 5, 6, 8, 10mm
Colour:	Black
Cloth/Plate Finish:	Plate
Density [specific gravity]:	1.21 g/cm ³
Hardness [Degrees Shore A]:	60° ± 5°
Tensile Strength [Mpa]:	22.0 min
Elongation at break :	610 %
Minimum Temperature :	-20°C
Maximum temperature:	+90°C
Compression Set :	24%
Abrasion resistance (mm ³):	36
Tear Resistance (kN/m) :	34.1

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied.



Certificate No: GB08/75575

This product is REACH, RoHS, PAH & CE Compliant.