

# BS2752-C60 Neoprene Rubber



## DRC26 DATA SHEET

**DELTA RUBBER LIMITED**

Unit 21 Priory Industrial Park, Airspeed Road  
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

### Description

DRC26 Black BS2752-C60 specification high quality Neoprene 60° shore A material, suitable for a wide range of applications with excellent general mechanical properties and resistance to oils & greases, water, ozone, mild chemicals, acids etc.

### Technical Information

Material:	Chloroprene BS specification grade
Application:	General Purpose, Water/UV/Oil/Fuel Resistant
Thickness:	0.5,1,1.5,2,3,5,6mm
Colour:	Black
Cloth/Plate Finish:	Plate
Density [specific gravity]:	1.40
Hardness [Degrees Shore A]:	60° ± 5°
Tensile Strength [MPA]:	13 min
Elongation at Break:	350%
Minimum Temperature:	-30°C
Maximum Temperature:	+120°C
Compression Set:	25%
Tear Resistance (kg/cm)	N/A

#### Thickness

0.5mm-6mm

(other thicknesses on request)

#### Sheet Size

1.4m wide x 5,10m rolls

#### Finish

Plate

#### Cutting

Standard Press Tools

