

SPECIFICATION SHEET



Fuel – grade Nitrile/PVC Rubber

**Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD
Tel: 01425 278011
Fax: 01425 278012
www.deltarubber.co.uk
deltasales@deltarubber.co.uk**

Technical Information

Material:	NBR/PVC, Nitrile CQ Rubber
Application:	Oil-based products/ fuel resistant / General purpose
Thickness:	1.5mm, 3mm, 6mm
Colour:	Black
Cloth/Plate Finish:	Plate / Plate
Compound:	NBR/PVCSBR
Density [specific gravity]:	1.25
Hardness [Degrees Shore A]:	65° ± 5°
Tensile Strength [Mpa]:	6.0
Elongation at break %:	250 %
Minimum Temperature :	-20°C
Maximum temperature:	+110°C
Compression Set 70°, 22hrs:	40%

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied.



This product is REACH, RoHS, PAH & CE Compliant.

Certificate No: GB08/75575

Directors: Martin Bailey, Jonathan Fisher

Registered in England No: 6033135

VAT No: GB 899 1951 52