

SIL16 Expanded Silicone Sheet



SIL16 DATA SHEET

DELTA RUBBER LIMITED

Unit 21 Priory Industrial Park, Airspeed Road
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

Description

Sil 16 expanded Silicone Sponge sheet is suitable for a range of applications. The material is suitable for use at temperatures up to +200°C and as low as -60°C. Silicone also has excellent resistance to ozone, oxidation, UV light and weathering in general.

Technical Information

*Apparent Density:	256 Kg/m ³
**Hardness:	42° Shore A
***Compression Stress 40% Strain:	90 kPa
***Compression Stress 25% Strain:	6.4 kPa
Tensile Strength:	0.6 Nmm ²
Elongation at break:	145%
Compression Set 50% compression 24 hours -	
22 hrs @70°C:	12%
22 hrs @100°C:	14.5%

* Density measured on 25mm diameter cord sample. The density of samples of different sizes will be different from that stated here.

** Hardness measured 10mm thick samples. At less than 10mm the measured hardness will increase with density.

*** Compression set measured on 25mm thick sample. The compressive stress of the material increases with the density as the sample thickness is reduced.

Thickness

0.8mm-12.70mm
(other thicknesses on request)

Sheet Size

.915m wide x 5, 10m
rolls

Cutting

Standard Press Tools

