

SPECIFICATION SHEET



Red/Pink Natural
Rubber - 40° shore

Unit 21
Priory Industrial Park
Airspeed Road
Christchurch Dorset
BH23 4HD

Tel: 01425 278011

Fax: 01425 278012

www.deltarubber.co.uk

deltasales@deltarubber.co.uk

Description

This material is the ultimate rubber for high wear & abrasion resistance. Specially compounded from 95% pure natural Latex, this material is recognised as the premium material developed for slurry & abrasive handling applications, chutes & tank linings, pipelines, hydro-cyclones and sumps, valves and pumps. A truly exceptional material.

- Material Profile: See Below
- Thickness: 1.5mm to 25mm (other thickness on request)
- Sheet size: 1.4m wide x 5,10 or 20m rolls
- Finish: Cloth-marked
- Cutting: Standard Tools

Technical Information

Material:	Red Natural Rubber
Application:	High Abrasion Resistance
Thickness:	.5mm, 3mm, 5mm, 6mm, 8mm, 10mm, 12mm, 15mm, 20mm,25mm
Colour:	Pink/Red
Cloth/Plate Finish:	Cloth/ Cloth
Compound:	NR
Density [specific gravity]:	0.98
Hardness [Degrees Shore A]:	40° ± 5°
Tensile Strength [Mpa]:	20.0
Elongation at break :	810 %
Minimum Temperature :	-20°C
Maximum temperature:	+70°C
Abrasion resistance (mm3):	80
Tear resistance (kg/cm):	20



Certificate No: GB08/75575