

SPECIFICATION SHEET



Tan Natural 45° shore Rubber.

Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD
Tel: 01425 278011
Fax: 01425 278012
www.deltarubber.co.uk
deltasales@deltarubber.co.uk

Description

This material has a very high abrasion resistance and elasticity, being classed as a 'Para-Natural' (or pure gum). Produced from natural Latex.

- **Material Profile: See Below**
- **Thickness: 1.5mm to 25mm (other thickness on request)**
- **Sheet size: 1.4m wide x 5,10 or 20m rolls**
- **Finish: Smooth plate**
- **Cutting: Standard Tools**

Technical Information

Material:	Natural Rubber
Application:	High Abrasion resistant
Thickness:	1.5mm, 3mm, 5mm, 6mm, 8mm, 10mm, 12mm, 15mm, 20mm, 25mm
Colour:	Tan
Cloth/Plate Finish:	Plate / Plate
Compound:	NR
Density [specific gravity]:	1.05
Hardness [Degrees Shore A]:	45° ± 5°
Tensile Strength [Mpa]:	16.0 min
Elongation at break :	600 %
Minimum Temperature :	-20°C
Maximum temperature:	+70°C
Abrasion resistance (mm ³):	83
Tear resistance (kg/cm):	25

The information given above is based upon average values and is no way intended as a warranty. The purchaser is deemed responsible for determining the suitability of the product for any particular application. All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable, but are provided for guidance purposes only. The Company holds no legal or contractual responsibility for information supplied.



Certificate No: GB08/7557

This product is REACH, RoHS, PAH & CE Compliant.

Directors: Martin Bailey, Jonathan Fisher

Registered in England No: 6033135

VAT No: GB 899 1951 52