

SPECIFICATION SHEET



DRN06 Commercial Quality Natural Rubber 65° shore A

Unit 21 Priory Industrial Park
Airspeed Road
Christchurch
Dorset
BH23 4HD
Tel: 01425 278011
Fax: 01425 278012
www.deltarubber.co.uk
deltasales@deltarubber.co.uk

Description

This material is a general purpose economy grade blended Natural/Styrene Butadiene rubber. May contain some reclaim material, minor surface imperfections & blemishes may occur.

- **Material Profile: See Below**
- **Thickness: 1.0mm to 10mm**
- **Sheet size: 1.4m wide x 5m/10m rolls**
- **Finish: Smooth**
- **Cutting: Standard Tools**

Technical Information

Material:	Natural Rubber / Styrene-Butadiene
Application:	General purpose
Thickness:	1.5mm, 2mm, 3mm, 4mm, 5mm, 6mm, 8mm, 10mm
Colour:	Black
Cloth/Plate Finish:	Plate / Plate
Compound:	NR/SBR
Density [specific gravity]:	1.6
Hardness [Degrees Shore A]:	65 ± 5°
Tensile Strength [Mpa]:	2.5
Elongation at break %:	130 %
Minimum Temperature :	-20°C
Maximum temperature:	+70°C
Abrasion resistance (mm ³):	N/A
Tear resistance (kg/cm):	N/A
Compression Set 70°, 22hrs:	60%



Certificate No: GB08/75575

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is implied or given in respect of the information. In any event our liability is limited to the invoice value of the goods delivered to you.